



Sealing - V ring
Phenolic thermal protector - manual
NDE sealing - V ring
Class F insulation - 80K temperature rise
NDE-bearing with double shield-ZZ
Shaft material - SAE/ABNT 1040/45
Rotation CW and CCW
DE-bearing with double shield-ZZ
Duty S1
Color Munsell N 1 matte black
Painting plan 207N
Service factor 1.15
Mounting F-1/B14R(D)

WEG ELECTRIC CORPORATION - WEC

		ACCORDING TO CLAIM 422506133	OSCARFLORES	GARTURO	AROJAS	02.01.2025	02
		ACCORDING TO CLAIM 421885764	ISAAVEDRA	RAMIREZC	MORALESR	04.09.2023	01
ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	ALVAREZZ	SINGLE PH. MOTOR ROLLED STEEL FRAME 56 IP55 TEFC		1321616789			
CHECKED	GARTURO			WDD	02		
RELEASED	EFRENZ						
REL. DATE	07.12.2022	WEG	HUEHUETOCA	[Ventas Exportacion]	SHEET	1 / 1	

1.5 HP 04 Poles 60 Hz 421676767

PRELIMINARY DOCUMENT - Not to be used for installation purposes. Dimensions in inches XME A3