



Velocidad maxima segura:6000 rpm/Max safe speed:6000 rpm					
Apto para trabajar para VFD 1000: 1 CT / Suitable to work for VFD 1000:1 CT					
Placa de identificación adicional para uso del inversor / Nameplate for VFD motor					
Termostato 155°C – Desconexión / Thermal protection to switch off – thermostat 155°C					
Material del eje – SAE/ABNT 1040/45 / Shaft material – SAE/ABNT 1040/45					
Vedación – Anillos V Ring / Sealing – V ring					
Dren automático de goma / Automatic rubber drain plug					
Color Munsell N 1 negro mate / Color Munsell N 1 matte black					
Plan de pintura 207N / Painting plan 207N					
Forma constructiva F-1/B34R(D) / Mounting F-1/B34R(D)					

WEG ELECTRIC CORPORATION - WEC

New drawing		OSCARFLORES	OSCARFLORES	OSCARPEREZ	08.04.2025	00		
ECM	LOC	SUMMARY OF MODIFICATIONS		EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	OSCARFLORES	THREE PH. MOTOR ROLLED STEEL PREM. EFF.						
CHECKED	OSCARFLORES	FRAME 56CZ IP55 TENV						
RELEASED	OSCARPEREZ							
REL. DATE	08.04.2025	WEG	HUEHUETOCA	[Ventas Exportacion]	SHEET	1 / 1		

1.5 HP 04 Poles 60 Hz 422614669

PRELIMINARY DOCUMENT - Not to be used for installation purposes. Dimensions in inches. XME A3

