



UNITS: INCHES

FRAME SIZE	MOUNTING				CONDUIT BOX				KEYSEAT
	E	2F	H	BA	AA	AB	AC	AS	R
256T	5.00	10.00	0.53	4.25	1.25	11.26	8.66	4.33	1.416

FRAME SIZE	MOTOR DIMENSIONS									
	A	B	C	D	G	J	K	O	P	T
256T	12.20	11.57	20.40	6.25	0.66	3.15	—	12.51	12.55	2.00

FRAME SIZE	SHAFT EXTENSION			KEY			BEARING NO		APPOX WEIGHT (lbs)
	N-W	U	V	WIDTH	THICKNESS	LENGTH	D.E	O.D.E	
256T	4.00	1.625	3.90	0.375	0.375	2.875	6310ZZ	6208ZZ	297

ALL DATA SUBJECT TO CHANGE WITHOUT NOTICE.
FOR CONSTRUCTION USE ONLY CERTIFIED DATA.

NOTES:

- 1.Dimension D tolerance:+0.00 inch
-0.06 inch
- 2.Dimension U tolerance:+0.000 inch
-0.001 inch
- 3.Dimension R tolerance:+0.000 inch
-0.015 inch
- 4.Dimension V is the length of straight part shaft

CERTIFIED DATA

CUSTOMER: _____ P.O. NO.: _____ TAG NO.: _____

MOTOR MODEL NO.: **0106DPPD11A-P** TOSHIBA FILE NO.: _____

HP: **10** RPM (SYN.): **1200** VOLTAGE: **230/460/796** Hz: **60**

FRAME SIZE: **256T** LOG NO.: _____ LOG REV. LEVEL: _____

REMARKS: _____

PER: _____ ISSUE DATE: _____ SUPERSEDES: _____

TOSHIBA INTERNATIONAL CORPORATION
Industrial Division / Houston Motor Plant

**SQUIRREL CAGE INDUCTION MOTOR
 PERFORMANCE SPECIFICATIONS**

INDEX	MPCF-1033
SHEET NO.	1 of 1
ISSUED	11/08/96
SUPERSEDES	10/06/95
REVISION	1
WRITTEN BY	R. EVANS
APPROVED BY	<i>Jay Bugbee</i>

Customer Tag:

CUSTOMER:
 TIC SR No.:
 Customer PO:

MOTOR NAMEPLATE DATA

H.P.: 10	VOLTS: 230/460/796	3 Ø / 60	Hz	S. RPM: 1200
FRAME: 256T	ENCL: ODP	FLAMPS: 27/13.5		FLRPM: 1120
FORM: DBK1	S.F.: 1.15	NEMA DESIGN: D		INSUL CLASS: F
TYPE: IKS	AMB.: 40	CODE: H		DUTY: CONT.
MODEL No.: 0106DPPD11A-P		kW:		Serial No.:
NOM. EFF.:	MIN. EFF.: -	P.F.: 83.5		

AMPERAGE Locked Rotor: 85.8	TORQUES FULL LOAD (lb-ft.): 46.40 LOCKED ROTOR (%): 378 BREAK DOWN (%): 410	** BEARINGS: Drive End: 6310ZZ Opposite Drive End: 6208ZZ
---------------------------------------	---	--

EFFICIENCY (%) FULL LOAD: 85.2 3/4 LOAD: 85.8 1/2 LOAD: 84.9	POWER FACTOR (%) FULL LOAD: 75.9 3/4 LOAD: 67.7 1/2 LOAD: 54.2
--	--

ALL CHARACTERISTICS ARE AVERAGE EXPECTED VALUES BASED UPON RATED VOLTAGE, FREQUENCY AND SINEWAVE POWER INPUT.

* TEMPERATURE RISE WILL BE CONSISTENT WITH INSULATION, AMBIENT AND SERVICE FACTOR AS DEFINED BY NEMA-MG-12.43 OR -20.40.

** BEARINGS ARE THE ONLY RECOMMENDED SPARE PART(S).

CERTIFIED BY:
DATE:

TOSHIBA

Reliability in Motion

TOSHIBA INTERNATIONAL CORPORATION

INDUSTRIAL DIVISION

PO BOX 40906

HOUSTON TX 77240

(713) 466-0277

(800) 231-1412

FAX (713) 466-8773

SPARE PARTS (RECOMMENDED)

OTHER THAN THE GREASE USED FOR RE-GREASABLE BEARINGS, **TOSHIBA** ADVISES THAT THERE ARE NO "USE" PARTS. THE ONLY INSURANCE SPARES THAT **TOSHIBA** SUGGESTS FOR THESE SQUIRREL CAGE INDUCTION MOTORS ARE INDUSTRY STANDARD, AND COMMERCIALY AVAILABLE ANTI-FRICTION BEARINGS, AS NOTED BELOW.

MOTOR COMPONENTS (SUCH AS TERMINAL BOXES, FAN COVERS, MACHINED PARTS) ARE AVAILABLE UPON SPECIAL REQUEST. IN THIS CASE, PLEASE ADVISE OUR ORDER ENTRY DEPARTMENT THE MODEL AND SERIAL NUMBERS (FOUND ON THE MOTOR NAMEPLATE) , AND A DESCRIPTION OF THE COMPONENT REQUIRED. THEY WILL THEN FURNISH THE CURRENT PART NUMBER, PRICE AND AVAILABILITY.

(NOTE: OUR INTERNAL PART NUMBERS ARE SUBJECT TO CHANGE WITHOUT NOTICE, AND ARE NOT PUBLISHED).

PLEASE ADVISE IF YOU HAVE ANY QUESTIONS.

CUSTOMER:

PURCHASE ORDER #

Customer Tag:

TOSHIBA FILE #

MODEL # 0106DPPD11A-P

HP / RPM / ENCL / FRAME: 10 / 1200 / ODP / 256T

DRIVE END BEARING: 6310ZZ

OPPOSITE DRIVE END BEARING: 6208ZZ

Prepared By:

Date: