


(1) 1/2-14 NPT (PLUGGED)

DASH NO.	"C"	"AD"	CAP. DASH	"XO"
500	9.84	6.94		
550	10.34	7.44		
600	10.84	7.94		
650	11.34	8.44	A	1.48
700	11.84	8.94	B	1.95
750	12.34	9.44	C	2.19

7/16-20 UNF-2A
R.H. THREAD
ECCENTRICITY OF THREADED
PORTION OF SHAFT IS HELD
WITHIN .004 T.I.R. WITH
INDICATOR ON O.D. OF GROUND
RING GAUGE BEING STATIONARY
WITH RESPECT TO THE MOTOR

			TOLERANCES UNLESS SPECIFIED		 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN	RDW 10/8/04		
			DEC.	INCHES		CHK			
			.X	±.1		APPD	SW 10/8/04		
			.XX	±.03		SCALE	3=8		
			.XXX	±.005	TITLE	OUTLINE - 56J FRAME DRIP PROOF - "C" FACE	REF		
01	REMOVED WIRING INSTRUCTION DECAL, ADDED AUTO DECAL	GWS 3/18/08	.XXXX	±.0005	MAT'L.	JET PUMP	FMF		
NO.	REVISION	BY & DATE	CHK	ANG ±1/2°	FINISH		PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP	10/8/04	CAD FILE	028634	SIZE	DRAWING NO.	REV.
			DIST	BRF-NLV			A	028634	01