


DASH NO.	"C"	"AD"
800	13.37	6.47
850	13.87	6.97
900	14.37	7.47
950	14.87	7.97

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

ALL-STAINLESS
 VITON CONDUIT BOX & COVER GASKETS
 VITON O-RINGS IN ENDBELL RABBETS & UNDER THRU BOLT HEADS
 VITON SHAFT SEALS
 BREATHING PLUGS IN CONDUIT BOX & L.E. ENDBELL
 ALL STAINLESS STEEL CONSTRUCTION

NO.	REVISION	BY & DATE	CHK	ANG	TOLERANCES UNLESS SPECIFIED		FINISH	MATERIAL	TITLE	DRAWN	RDW	REV.		
					DEC.	INCHES								
03	BASE LOCATION DIM.2.88 CHANGED TO C-FACE	PVR 10/31/13	JD						 ELECTRIC MOTORS GEARMOTORS AND DRIVES		9/7/04			
02	REVISED PER ECR 91065, DECREASED "AD" DIM BY .09" AND CORRECTED "AD"	JWM 3/23/07		.X	±.1					CHK				
01	"AD" VALUE 6.06 W 6.12, 6.56 W 6.62, 7.06 W 7.12, 7.56 W 7.62; ECR 66947	KLS 5/26/06		.XX	±.03					APPD	SW	9/7/04		
				.XXX	±.005					SCALE		1=2		
				.XXXX	±.0005				REF		PRO40212			
									FMF					
									PREV					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT								RFP	9/7/04	CAD FILE	028622	SIZE	DRAWING NO.	REV.
								DIST				B	028622	03