



030187



FRAME	"C"	"L"	"AD"
JS56	10.31	4.19	2.94
LS56	10.81	4.69	3.44
NS56	11.31	5.19	3.94
RS56	11.81	5.69	4.44

CAPACITOR CASE
WHEN REQ'D.

NOTE:

SCREW HEADS ON RESILENT CLAMPS MUST
BE ON NAMEPLATE SIDE OF MOTOR.

				TOLERANCES UNLESS OTHERWISE SPECIFIED		LEESON ELECTRIC CORPORATION					
				DECIMALS							
03	ADDED NOTES FOR RIBS ON BASE	ARV	3/24/11	.00	± .01	DRAWN P.G. 8/26/82	TITLE OUTLINE – OPEN DRIP PROOF – S56 FRAME RESIL.				
02	REDREW BASE	ARV	4/16/08	.000	± .005	CH’K’D. ADH 8/30/82					
01	REDRAWN TO CURRENT STANDARDS	PG	DBT	4/1/97	.0000	± .0005	APPR. JEW 8/30/82	MAT’L. BRF			
NO.	REVISION	BY	DATE	FRACTIONS	± 1/64	SCALE 3=8					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED				ANGLES	± 1/2°	REF. 030006	FINISH		SIZE	DRAWING NO.	
				INCH/MM		FMF 4P17DJ5	AUTO PARKING		A	030187	