


- NOTES:  
 1. CONDUIT BOX BE ROTATED IN 90° STEPS.  
 2. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	2XF	BS
1275	284TS	12.50	24.96	9.50		4.75
1425	284/6TS	13.00	26.46	11.00	9.50	5.50

		TOLERANCES UNLESS SPECIFIED		 ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN RJW 09-25-2008	
		DEC.	INCHES			CHK ML 09-25-2008	
		.X	±.1	TITLE OUTLINE - TFNA - CAST C'BOX		APPD BW 09-25-2008	
		.XX	±.03	280TS FR. - TEFC - STD 12.50 LAM.		SCALE 1=4.5	
		.XXX	±.005	FINISH		REF	
		.XXXX	±.0005	MAT'L		FMF MU87709	
NO.	REVISION	BY & DATE	CHK	ANG	±7'30°	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	09-25-2008	CAD FILE	SS311062LE
				DIST	LB	SIZE	DRAWING NO. PAGE OF REV.
						B	SS311062LE