



NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	2FF	BS
1525	404T	14.75	35.62	12.25		6.12
1675	404/405T	16.25	37.14	12.25	13.75	6.88

		TOLERANCES UNLESS SPECIFIED		ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN KL 02-16-2004	
		DEC INCHES				CHK ML 02-16-2004	
		X ±.1		TITLE OUTLINE - TEFC		APPR JES 02-16-2004	
		.XX ±.03		400T FR. - TAPPED LEAD HOLE		SCALE 1:5	
		.XXX ±.005		MATL		REF SS508859	
1	UPDATED FRAME & REDRAWN IN SOLIDWORKS MU102119	JSB	09-13-2011	JB	XXXXX ±.0005	PAGE OF	
NO REVISION		BY & DATE		CHK ANG ±1/2°	FINISH	PAGE OF	
THIRD ANGLE PROJECTION		RFP	05-22-1988	PREV	SIZE	DRAWING NO	REV
		NETWORK FILE NAME		SS508859LE	B	SS508859LE	1