

UNITS: INCHES

FRAME SIZE	MOTOR DIMENSIONS										CONDUIT BOX							
	A	B	C	D	G	J	K	M	O	P	T	AA	AB	AC	AE	AF	XL	XN
213T/215T	10.4	8.7	19.5	5.25	1.0	2.0	0	6.9	11.4	11.2	2.0	1.00	11.3	8.8	5.25	2.8	7.0	6.1

FRAME SIZE	MOUNTING					SHAFT EXTENSION					KEY SEAT			BEARINGS			MAXIMUM WEIGHT								
	E	2F	H	BA	N-W	V	U	R	S	ES	LS	OS	213T/215T <th>4.25 <th>5.50/7.00 <th>0.44 <th>3.50 <th>3.38 <th>3.12 <th>1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th></th></th></th></th></th></th></th>	4.25 <th>5.50/7.00 <th>0.44 <th>3.50 <th>3.38 <th>3.12 <th>1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th></th></th></th></th></th></th>	5.50/7.00 <th>0.44 <th>3.50 <th>3.38 <th>3.12 <th>1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th></th></th></th></th></th>	0.44 <th>3.50 <th>3.38 <th>3.12 <th>1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th></th></th></th></th>		3.50 <th>3.38 <th>3.12 <th>1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th></th></th></th>	3.38 <th>3.12 <th>1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th></th></th>	3.12 <th>1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th></th>	1.375 <th>1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th></th>	1.201 <th>0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th></th>	0.312 <th>2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th></th>	2.38 <th>6308UU <th>6208UU <th>180 lbs.</th> </th></th>	6308UU <th>6208UU <th>180 lbs.</th> </th>
213T/215T	4.25	5.50/7.00	0.44	3.50	3.38	3.12	1.375	1.201	0.312	2.38	6308UU	6208UU	180 lbs.												

CUSTOMER: \_\_\_\_\_ MOTOR MODEL NO.: \_\_\_\_\_ TAG NO's: \_\_\_\_\_

P.O. NO.: \_\_\_\_\_ HP: \_\_\_\_\_ VOLTAGE: \_\_\_\_\_ RPM(SYN.): \_\_\_\_\_ Hz: \_\_\_\_\_  
 FRAME SIZE: \_\_\_\_\_ PRODUCT TYPE: IEF3 EQP III, EPACT, & HIGH EFFICIENCY  
 COMMENTS: \_\_\_\_\_

PER: \_\_\_\_\_ DATE: \_\_\_\_\_

TOSHIBA RESERVES THE RIGHT TO MAKE CHANGES OF TECHNICAL IMPROVEMENT AND THE DATA MAY CHANGE WITHOUT NOTICE  PRELIMINARY  
 DO NOT USE FOR CONSTRUCTION, INSTALLATION, OR APPLICATION PURPOSES UNLESS THE DRAWING IS MARKED AS CERTIFIED  CERTIFIED

- STANDARD (NO AUX. BOXES)
- RTD AUX. BOX
- SPACE HEATER AUX. BOX
- BEARING RTD's

- NOTES:
- DIMENSION V REPRESENTS LENGTH OF STRAIGHT PART OF SHAFT
  - MAIN CONDUIT BOX MAY BE ROTATED IN 90° INCREMENTS
  - KEY DIMENSIONS EQUAL S x S x 2.38 (MOTOR SUPPLIED WITH KEY)
  - MOTOR WEIGHT SHOWN IS MAXIMUM HORSEPOWER IN FRAME
  - THIS DIMENSION EQUALS 2F FOR 213T MOUNTING
  - STANDARD PRODUCT USE BI-DIRECTIONAL FAN. OPPOSITE ROTATION AVAILABLE ONLY BY CONNECTION CHANGE

**TOSHIBA**  
 TOSHIBA INTERNATIONAL CORPORATION

TOTALLY-ENCLOSED FAN-COOLED  
 HORIZONTAL FOOT-MOUNTED  
 3 PHASE INDUCTION MOTOR  
 F1 ASSEMBLY

**XT SERIES**  
 VISIT OUR WEBSITE AT:  
 www.toshiba.com/ind

**TYPICAL MOTOR PERFORMANCE DATA**

Model: B0056FLF2AMH04

HP	kW	Pole	FL RPM	Frame	Voltage	Hz	Phase	FL Amps
5	3.7	6	1165	215T	230/460	60	3	14/7
Enclosure	IP	Ins. Class	S.F.	Duty	NEMA Nom. Eff.	NEMA Design	kVA Code	Ambient (°C)
TEFC	44	F	1.15	CONT	90.2	B	J	40 C

Load	HP	kW	Amperes	Efficiency (%)	Power Factor (%)
Full Load	5	3.7	6.5	90.1	79.4
¾ Load	3.75	2.8	5.5	89.7	72.7
½ Load	2.50	1.9	4.6	87.4	60.6
¼ Load	1.25	0.9	3.9	77.2	38.6
No Load			3.1		9.6
Locked Rotor			46.00		50.8

Torque				Rotor wk <sup>2</sup> Inertia (lb-ft <sup>2</sup> )
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	
22.5	310	375	400	1.60

Safe Stall Time(s)		Sound Pressure dB(A) @ 1M	Bearings*		Approx. Motor Weight (lbs)
Cold	Hot		DE	NDE	
32	15	-	6308UU	6208UU	

\*Bearings are the only recommended spare part(s).

**Motor Options:**  
Product Family:EQPIII  
Mounting:Footed,Shaft:T Shaft

Customer	
Customer PO	
Sales Order	
Project #	

Tag:

All characteristics are average expected values.

**TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.**


Engineering	aacosta	Doc. Written By	D. Suarez	Doc.# / Rev	MPCF-1119 / 0
Engr. Date	7/9/2012	Doc. Approved By	M. Campbell	Doc. Issued	6/8/2011

**SPEED TORQUE/CURRENT CURVE**

Model: B0056FLF2AMH04

HP	kW	Pole	FL RPM	Frame	Voltage	Hz	Phase	FL Amps
5	3.7	6	1165	215T	230/460	60	3	14/7
Enclosure	IP	Ins. Class	S.F.	Duty	NEMA Nom. Eff.	NEMA Design	kVA Code	Ambient (°C)
TEFC	44	F	1.15	CONT	90.2	B	J	40 C
Locked Rotor Amps	Rotor wk <sup>2</sup> Inertia (lb-ft <sup>2</sup> )	Torque						Break Down (%)
		Full Load (lb-ft)	Locked Rotor (%)	Pull Up (%)				
46.00	1.60	22.5	310	375			400	

**Design Values**



Customer		wk <sup>2</sup> Load Inertia (lb-ft <sup>2</sup> )	-
Customer PO		Load Type	-
Sales Order		Voltage (%)	100
Project #		Accel. Time	-

Tag:

All characteristics are average expected values.

**TOSHIBA INTERNATIONAL CORPORATION · HOUSTON, TEXAS U.S.A.**

Engineering	aacosta	Doc. Written By	D. Suarez	Doc.# / Rev	MPCF-1121 / 0
Engr. Date	7/9/2012	Doc. Approved By	M. Campbell	Doc. Issued	6/8/2011


### Motor Connection Diagrams 9 Leads

#### Across-the-Line Starting / Running Connections

Low Voltage Wye



High Voltage Wye



Switch L1 and L2 to reverse rotation