

NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 164303 CUST. PN: B128 HP: 1.0 SF: 1.40 ROT: CCWPE RPM: 3450 TYPE: CX FORM: - VOLTS: 230/115 AMP: 5.0 FRAME: M 56 J PH: 1 HZ: 60 INS: B DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED	LOW VOLTAGE HIGH VOLTAGE BROWN → B WHITE → B WHITE → L1 L1 → LINE WHITE → L2 L2 → LINE BROWN → A BROWN → A *A NON-REVERSIBLE	1. PILOT DIAMETER IS CONCENTRIC WITH SHAFT CENTERLINE WITHIN .004[.10] T.I.R. 2. FACE OF MOUNTING FLANGE IS PERPENDICULAR TO SHAFT CENTERLINE WITHIN .004[.10] T.I.R. 3. SHAFT RUNOUT NOT TO EXCEED .002[.05] 4. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST 5. ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS.

DRAWN BY: T.TOMI		Regal Beloit America, Inc.
CHECKED BY: JAN 27-2008	DESCRIPTION	
APPROVED BY:		
DATE:	MODEL - PFHP - 56FR OUTLINE	
REFERENCE:	MATERIAL	PROCESS/FINISH
THIRD ANGLE PROJECTION	SIZE/TOLG NO	SHEET
	C	B128
		1

DRAWING REVISION	REASON BY	DATE
E	P. CAVAS	12-08-2014
	APPROVED BY	DATE
	T. REYES	12-08-2014
ECO-0066332		
ECO DESCRIPTION		
CHANGED TITLE BLOCK		

16345211			-	
UL COMPONENT		CSA		
FILE#	CCN#	FILE#	GUIDE#	
E14663	XEWR23	LR4642	4211-01	
CUSTOMER	DISTRIBUTION			