



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 196263 CUST PN: B2748 HP: 2.0 SF: 1.3 ROT: CCWPE RPM: 3450 TYPE: CX CODE: G FORM: KJM FRAME: Y 56 Y VOLTS: 230 AMPS: - MAX AMPS: - SF AMPS: 11.5 PH: 1 HZ: 60 INS: F AMB: 50 °C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED	<p>USE COPPER CONDUCTORS ONLY. INSTALL MOTOR WITH VENTS DOWN. ACCEPTABLE FOR FIELD WIRING</p>	<ol style="list-style-type: none"> FOR THREADED SHAFT EXTENSION ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHIN .004 [.10] TOTAL GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR. END PLAY NOT TO EXCEED .010 [.25] MEASURED WITH NO THRUST. FINISH PAINT TO BE BLACK. REFERENCE MODEL: B748

PERFORMANCE CURVE	APPROVED SAMPLE		
15593311	0601158		
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
PENDING	PENDING	PENDING	PENDING
CUSTOMER	DSITRIBUTION		

DRAWING REVISION: F	REVISION BY: J.AGUILERA	DATE: 02-11-2015	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY: BL	Regal Beloit America, Inc.
ECO: 0068888	APPROVED BY: D.VALENCIANO	DATE: 02-11-2015	DEC. INCH mm ANGLE	DATE: 09-01-2009	
ECO DESCRIPTION: SEE ECO			.XX ±0.02 [±0.51]	APPROVED BY: SH	DESCRIPTION: MODEL-CFHP-56FR OUTLINE
			.XXX ±0.005 [±0.127]	DATE: 09-01-2009	MATERIAL: _____
			.XXXX ±0.0005 [±0.0127]	REFERENCE: _____	PROCESS/FINISH: _____
			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/3.81]	THIRD ANGLE PROJECTION	SIZE DWG NO: C B2748
			CORNER FILLETS .02 [1.51]		SHEET: 1
			MACHINED SURFACES $\sqrt{125}$ INCH mm $\sqrt{32}$		
			mm SHOWN IN [BRACKETS]		