

Centurion

1/2-14 N.P.S.M. WITH CAP

13.883 ± 0.055
[352.63 ± 1.40]

(5.30)
[(134.6)]

(11.90)
[(302.2)]

(5.32)
[(135.2)]

(.19)
[(4.8)]

.91
[23.0]

.401
[10.14]

.411
[10.19]

(.50)
[(12.7)]

EXTERNAL THREADS
1/2-20 UNF-2A
R.H. THREADS

Ø.6250
Ø.6235
Ø.5.874
Ø.5.861

Ø.002

Ø.004 C

Ø.004 C

Ø.006 C

Ø.7.125
[Ø180.98]
B.C.

Ø.440
[Ø11.18]

Ø.5.753
[Ø146.11]

Ø.5.750
[Ø146.04]

Ø.004 C

2.50
[63.5]

175367-30

USE COPPER CONDUCTORS ONLY.
INSTALL MOTOR WITH VENTS DOWN.
ACCEPTABLE FOR FIELD WIRING

175367-30

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

2

1

HOJA: 1

