




DASH	FR.	C	XB	BS
856	56	12.85	5.00	5.18

NOTE:

1. CONDUIT BOX CAN BE ROTATED 180°
2. MOTOR MUST BE ROTATED TO .75" STRIP SOCKET CLEARANCE FOR GROUND SCREW, MAXIMUM (10 DEGREES).

* DIMENSION IS FROM RESILIENT RING END CAP TO END OF SHAFT

				TOLERANCES UNLESS SPECIFIED			DRAWN PKG 06-06-1997			
				DEC.	INCHES		CHK ML 06-17-1997			
				.X	±.1		APPD GK 06-17-1999			
				.XX	±.03	TITLE OUTLINE 56 FR.-1Ø-BB-DR.PR.-RESIL. MT.	SCALE 11=32			
9	REDRAWN IN AUTOCAD	TAT 09-01-2004	ML	.XXX	±.005		REF			
8	REDRAWN ON CADD AND ADDED NOTE CN 24678	PKG 06-17-1997		.XXXX	±.0005	MAT'L.	FMF			
NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH	PREV			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP			CAD FILE 100122	SIZE	DRAWING NO.	PAGE OF	REV.
			DIST WP				A	100122	9	