



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: S48A10A01 CUST. PN: BN24V1 HP: 75 SF: 1.0 ROT: CCWPE RPM: 3450 TYPE: SP FORM: M VOLTS: 115 AMPS: 9.4 MAX. AMPS: 9.4 SF AMPS: 9.4 PH: 1 INS: B DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED		1. LEAD END FRAME TO BE ORIENTED TO DRIVE END FRAME TO WITHIN ±2. 2. ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS.

PERFORMANCE CURVE	APPROVED SAMPLE
S48J2W44	0801389
UL COMPONENT	CSA
FILE#	FILE#
PENDING	PENDING
PENDING	PENDING
CUSTOMER	DISTRIBUTION

FORMING REVISION	REVISION BY	DATE	REVISION	DATE	REVISION
ECO-0001384	F. HANNA	03-16-2016	ECO-0001384	03-16-2016	ECO-0001384
SEE ECO	O.H.E.		SEE ECO		SEE ECO

TOLERANCES UNLESS SPECIFIED	INCH	MILL	ANGLE
X	±2.5	±0.10	±0.5°
XXX	±0.130	±0.0051	
XXXX	±0.0130	±0.00051	
EDGES	0.0130	0.00051	SHARP
CORNER FILLETS	0.0130	0.00051	
MACHINED SURFACES	0.0015	0.020	
FINISH	INCH	MM	
	1/32	0.8	

DESIGN BY	DATE	DESCRIPTION
Regal Beloit America, Inc.		MODEL - PFHP - 48FR
		OUTLINE
		PROCESS/FINISH

SCALE	SHEET
1/4" = 1"	1