



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED IN OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°. THIS MODIFICATION CAN BE PERFORMED ONLY BY THE ORIGINAL EQUIPMENT MANUFACTURER, OR BY A FACILITY THAT IS COVERED UNDER UNDERWRITERS LABORATORIES INC. CATEGORY PTKQ, TITLED "MOTOR AND GENERATORS., REBUILT FOR USE IN HAZARDOUS LOCATION".
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1212	213/215	23.45	11.76	10	7	5	20.11
912	213/215	20.45	8.63	7	5.5	3.5	17.11
DASH	FRAME	C	B	2F	2FF	BS	AG

				TOLERANCES UNLESS SPECIFIED				DRAWN PN 9/2/2010		
				DEG INCHES				CHK AK 9/2/2010		
				X ±.1		TITLE OUTLINE		APPR		
				XX ±.02		210 FR. - EPFC		SCALE 1:8		
				XXX ±.005		MAT'L		REF 037660		
01	'B' DIM UPDATED IN TABLE AS PER ISAAC 12-0460			GR	3/16/2012	SR	XXXX ±.0005	FMF		
NO	REVISION			BY & DATE		CHK	ANG ±7°30"	PREV		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT								RFP	CAD FILE 037702	
								SIZE	DRAWING NO	REV
								B	037702	01
								DIST	LB - MT2	