




Grounding for leads 5.2-25 mm<sup>2</sup> / 10-4 AWG

- Without Space Heaters
- DE roller bearing
- Slinger ring supplied loose
- Sealing - INPRO/SEAL
- Tirrol oil applied on endshields fittings
- Type "T" threaded drain plug
- Nameplate with API 661 marking
- Grease outlet according to IEEE841
- Slinger ring on shaft end
- Shaft locking device
- Shaft material - AISI/SAE 4140
- Color RAL 5009
- Painting plan 222E
- Mounting NEMA W-8
- Mounting V6R(D)



DM12 WEG WPR-7339

20 HP 06 Poles 60 Hz						A
<b>WEG HOUSE ACCOUNT MOTORS</b>						
UPD CENTER HOLE THREAD - CLAIM 422471286			NOERNBERG	NOERNBERG	DECIOP	22.11.2024 01
INITIAL ISSUE - CLAIM 421953630			NOERNBERG	NOERNBERG	MARLONN	02.08.2023 00
ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE VER
EXECUTED	NOERNBERG	THREE PH. MOTOR IEEE 841 W22 NEMA PREM. EFF. FRAME 284/6T IP56 TEFC		1413579213		
CHECKED	NOERNBERG					
RELEASED	MARLONN					
REL. DATE	02.08.2023	WMO JARAGUA DO SUL	[Engenharia de Produto]	WDD	01	SHEET 1 / 1