



C

D

E

Power	Polarity	L	C
1 HP	4P	7.874	11.473
0.75 HP	4P	7.087	10.685
0.5 HP	4P	6.693	10.291

- Outlet leads directed to down when looking at shaft end
- Sealing - Stainless steel viton oil seal ring
- Stainless steel screws - AISI 304
- 2RS NDE ball bearing
- Permatex sealed endshields
- Tropicalized internal painting
- 2RS DE ball bearing
- Shaft material - stainless steel AISI 304
- Class F insulation - 80K temperature rise
- AISI 304 stainless steel nameplates
- Painting plan 205E
- Service factor 1.15
- Mounting F-1/B3R(D)

		According to claim ZC 423027306	ELIZABETH	RIOMIGUEL	RIOMIGUEL	26.01.2026	03
		According to claim ZC 423027306	ELIZABETH	RIOMIGUEL	RIOMIGUEL	26.01.2026	02
ECM	LOC	SUMMARY OF MODIFICATIONS	EXECUTED	CHECKED	RELEASED	DATE	VER
EXECUTED	OSCARFLORES	THREE PH. MOTOR ROLLED STEEL HYDROWASH PREM. EFF. FRAME 56 IP56 TENV					
CHECKED	RAMIREZC						
RELEASED	FMONROY						
REL. DATE	05.02.2025		WEG HUEHUETOCA [Ventas Exportacion]				

1652053764
WDD 03
SHEET 1 / 1

PRELIMINARY DOCUMENT - Not to be used for installation purposes. Dimensions in inches XME A3