



TERM.  
END

NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90 ° STEPS.
2. CONDUIT BOX CAN BE MOUNTED IN OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1212	213/215	22.63	11.76	10	7	5
912	213/215	19.63	8.63	7	5.5	3.5
DASH	FRAME	C	B	2F	2FF	BS

		TOLERANCES UNLESS SPECIFIED				DRAWN AK 10/05/2009	
		DEC	INCHES			CHK SK 10/05/2009	
		X	±.1	TITLE OUTLINE		SCALE 1:8	
		XX	±.02	210.FR - TEFC		REF	
		XXX	±.005	MATL		FMF	
01	UPDATED PER IS12-0462	GR	2/15/2012	PN	XXXX ±.0005	PREV	
NO REVISION		BY & DATE		CHK	ANG ±7.30°	FINISH	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE 037659		SIZE
				DIST	LB - MT2	DRAWING NO	
						B	
						037659	
						REV	
						01	