

1. BOX CAN BE ROTATED IN 90° STEPS.
2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FR.	C	B	BS	2F	2FF	FOOT HOLE QTY	MOUNTING
1150	324TS	27.37	13.00	5.25	—	10.50	4	F1 OR F2
1300	324/6TS	28.87	14.50	6.00	10.50	12.00	8	F1 OR F2
1450	326TS	30.37	15.00	6.75	12.00	13.50	8	F1 OR F2

15	ADDED GROUND SCREW HOLE	RJW 06-07-2005	ML	TOLERANCES UNLESS SPECIFIED		DRAWN	RW 01-12-1993					
14	REVISED DASH 1450 2FF WAS 12.00 CN33798	RJW 03-22-2005	ML	DEC.		INCHES	CHK	ML 01-12-1993				
13	ADDED DASH 1450 CN33599	TAT 08-03-2004	ML	X		±.1	APPD	GK 01-12-1993				
12	ADDED FOOT HOLE QTY. & MTG. TO TABLE CN37323	TAT 12-09-2003	ML	.XX		±.03	SCALE	3=16				
11	UPDATED C'BOX GEOMETRY CN28424	DRS 01-06-2000		.XXX		±.005	REF					
10	RE-ISSUE ADDED HOLE SIZE CN26835	CAE 04-28-1999		.XXXX	±.0005	MAT'L	FMF					
NO.	REVISION	BY & DATE	CHK	ANG	±7°30"	FINISH	PREV					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						CAD FILE	ss28706	SIZE	DRAWING NO.	PAGE	OF	REV.
								B	SS28706			15