


DUTY MASTER ALTERNATING CURRENT MOTORS
SQUIRREL-CAGE INDUCTION

ENCLOSURE: TOTALLY ENCLOSED
MOUNTING: FOOT
COOLING: FAN COOLED

FRAMES 250T THRU 440T



DIMENSIONS ARE IN INCHES; SEE SHEET 2 FOR DIMENSIONS IN MILLIMETERS															
FRAME	A	D(2)	E	G	H	J	K	O	P	T	STEEL TERMINAL BOX				EV
											AA	AB	AC	AF	
254T-256T	12.50	6.25	5.00	.75	.56	2.50	---	13.25	13.25	2.44	1-1/4	10.75	8.75	2.50	4.25
284T-286TS	13.75	7.00	5.50	.75	.56	2.50	---	14.75	14.88	2.44	1-1/2	12.75	10.00	3.19	4.75
324T-326TS	15.50	8.00	6.25	.88	.69	2.75	4.50	16.69	17.00	2.44	2	15.19	11.44	4.25	5.25
364T-365TS	17.00	9.00	7.00	.88	.69	2.75	3.88	18.50	19.50	2.94	3	18.06	14.00	5.38	5.88
404T-405TS	19.00	10.00	8.00	1.12	.81	3.25	4.62	21.31	22.50	2.94	3	19.31	15.25	5.38	6.62
444T-445TS	21.00	11.00	9.00	1.12	.81	3.25	5.25	23.38	25.25	3.25	3	23.38	18.12	6.50	7.50
(1)															1.25

FRAME	C	BS	B	2F	(4) 2XF	N	SHAFT AND KEY				WEIGHT LBS. (5)
							N-W(6)	U(3)	V	SQ.	LGTH.
254T	24.56	5.00	12.00	---	8.25	4.12	4.00	1.625	3.75	.375	2.88
256T	24.56	5.00	12.00	10.00	---	4.12	4.00	1.625	3.75	.375	2.88
284T	27.44	5.50	13.00	---	9.50	5.00	4.62	1.875	4.38	.500	3.25
284TS	26.06	5.50	13.00	---	9.50	5.00	4.62	1.875	4.38	.500	3.25
286T	27.44	5.50	13.00	11.00	---	5.00	4.62	1.875	4.38	.500	3.25
286TS	26.06	5.50	13.00	11.00	---	5.00	4.62	1.875	4.38	.500	3.25
324T	30.44	6.00	14.75	---	10.50	5.62	5.25	2.125	5.00	.500	3.88
324TS	28.94	6.00	14.75	---	10.50	5.62	5.25	2.125	5.00	.500	3.88
326T	30.44	6.00	14.75	12.00	---	5.62	5.25	2.125	5.00	.500	3.88
326TS	28.94	6.00	14.75	12.00	---	5.62	5.25	2.125	5.00	.500	3.88
364T	33.44	6.12	15.00	---	11.25	6.25	5.88	2.375	5.62	.625	4.25
364TS	31.31	6.12	15.00	---	11.25	6.25	5.88	2.375	5.62	.625	4.25
365T	33.44	6.12	15.00	12.25	---	6.25	5.88	2.375	5.62	.625	4.25
365TS	31.31	6.12	15.00	12.25	---	6.25	5.88	2.375	5.62	.625	4.25
404T	38.31	6.88	16.00	---	12.25	7.50	7.25	2.875	7.00	.750	5.62
404TS	35.31	6.88	16.00	---	12.25	7.50	7.25	2.875	7.00	.750	5.62
405T	38.31	6.88	16.00	---	12.25	7.50	7.25	2.875	7.00	.750	5.62
405TS	35.31	6.88	16.00	13.75	---	7.50	7.25	2.875	7.00	.750	5.62
444T	44.62	8.25	19.00	---	14.50	8.94	8.50	3.375	8.25	.875	6.88
444TS	40.88	8.25	19.00	---	14.50	8.94	8.50	3.375	8.25	.875	6.88
445T	44.62	8.25	19.00	16.50	---	8.94	8.50	3.375	8.25	.875	6.88
445TS	40.88	8.25	19.00	16.50	---	8.94	8.50	3.375	8.25	.875	6.88
(1)						5.19	4.75	2.375	4.50	.625	3.00

- (1) SPECIAL DIMENSIONS APPLYING TO THIS ORDER ON THIS LINE.
- (2) "D" VARIES — 250T - 320T +.00, -.03.
360T - 440T +.00, -.06.
- (3) "U" VARIES — UP TO 1.625 DIA. +.0000, -.0005
1.625 AND LARGER +.000, -.001.
- (4) ALL FRAMES HAVE EIGHT MOUNTING HOLES FOR DUAL MOUNTING.
- (5) MOTOR WEIGHTS MAY VARY BY 15% DEPENDING UPON RATING.
- (6) "N-W" VARIES +.00, -.25.
- FRAME- TYPE- CERTIFIED FOR-
ORDER- ITEM- HP- RPM- PH- HZ- VOLTS-
RELANCE SALES ORDER- APPROVED BY- DATE
- CONDUIT BOX LOCATED ON OPPOSITE SIDE WHEN F-2-W-1,
W-4-W-5-W-7, OR C-1 MOUNTING IS SPECIFIED.
- IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT
FACTORY.
- MAXIMUM PERMISSIBLE SHAFT RUNOUT WHEN MEASURED
AT END OF STD. SHAFT EXTENSION IS .002 T.I.R. UP TO
AND INCLUDING 1.625 DIA. AND .003 T.I.R. 1.625 DIA.
TO 5 INCH DIA.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: UPDATE TITLE SHEET 2		
REV. LTR: B	VERSION: 02	TDR: 000000498266
FILE: \RAG\00000\167		REVISED: 07:05:46 04/29/2009
MTL: -		BY: RAGEC

Baldor • Dodge • Reliance

DIM SHEET 250T THRU 440T
SH 1 of 1