


DUTY MASTER ALTERNATING CURRENT MOTORS
SQUIRREL-CAGE INDUCTION

ENCLOSURE: TOTALLY ENCLOSED
MOUNTING: FOOT
COOLING: FAN COOLED

FRAMES 250T THRU 440T



DIMENSIONS ARE IN INCHES; SEE SHEET 2 FOR DIMENSIONS IN MILLIMETERS

FRAME	A	D(2)	E	G	H	J	K	O	P	T	STEEL TERMINAL BOX					EV
											AA	AB	AC	AF	BA	
254T-256T	12.50	6.25	5.00	.75	.56	2.50	--	13.25	13.25	2.44	1-1/4	10.75	8.75	2.50	4.25	1.00
284T-286TS	13.75	7.00	5.50	.75	.56	2.50	--	14.75	14.88	2.44	1-1/2	12.75	10.00	3.19	4.75	1.00
324T-326TS	15.50	8.00	6.25	.88	.69	2.75	4.50	16.69	17.00	2.44	2	15.19	11.44	4.25	5.25	1.36
364T-365TS	17.00	9.00	7.00	.88	.69	2.75	3.88	18.50	19.50	2.94	3	18.06	14.00	5.38	5.88	1.36
404T-405TS	19.00	10.00	8.00	1.12	.81	3.25	4.62	21.31	22.50	2.94	3	19.31	15.25	5.38	6.62	1.13
444T-445TS	21.00	11.00	9.00	1.12	.81	3.25	5.25	23.38	25.25	3.25	3	23.38	18.12	6.50	7.50	1.25

(1)

FRAME	SIZE	C	BS	B	2F	(4) 2XF	N	SHAFT AND KEY					WEIGHT LBS. (5)
								N-W(6)	U(3)	V	SQ.	LGTH.	
254T	24.56	5.00	12.00	---	---	8.25	4.12	4.00	1.625	3.75	.375	2.88	305
256T	24.56	5.00	12.00	10.00	---	---	4.12	4.00	1.625	3.75	.375	2.88	315
284T	27.44	5.50	13.00	---	---	9.50	5.00	4.62	1.875	4.38	.500	3.25	435
284TS	26.06	5.50	13.00	---	---	9.50	5.00	3.62	1.625	3.00	.375	1.88	435
286T	27.44	5.50	13.00	11.00	---	---	5.00	4.62	1.875	4.38	.500	3.25	450
286TS	26.06	5.50	13.00	11.00	---	---	3.62	3.25	1.625	3.00	.375	1.88	450
324T	30.44	6.00	14.75	---	---	10.50	5.62	5.25	2.125	5.00	.500	3.88	540
324TS	28.94	6.00	14.75	---	---	10.50	4.62	3.75	1.875	3.50	.500	2.00	540
326T	30.44	6.00	14.75	12.00	---	---	5.62	5.25	2.125	5.00	.500	3.88	580
326TS	28.94	6.00	14.75	12.00	---	---	4.12	3.75	1.875	3.50	.500	2.00	580
364T	33.44	6.12	15.00	---	---	11.25	6.25	5.88	2.375	5.62	.625	4.25	800
364TS	31.31	6.12	15.00	---	---	11.25	4.12	3.75	1.875	3.50	.500	2.00	794
365T	33.44	6.12	15.00	12.25	---	---	6.25	5.88	2.375	5.62	.625	4.25	840
365TS	31.31	6.12	15.00	12.25	---	---	4.12	3.75	1.875	3.50	.500	2.00	834
404T	38.31	6.88	16.00	---	---	12.25	7.50	7.25	2.875	7.00	.750	5.62	1120
404TS	35.31	6.88	16.00	---	---	12.25	4.50	4.25	2.125	4.00	.500	2.75	1111
405T	38.31	6.88	16.00	---	---	12.25	7.50	7.25	2.875	7.00	.750	5.62	1160
405TS	35.31	6.88	16.00	13.75	---	---	4.50	4.25	2.125	4.00	.500	2.75	1151
444T	44.62	8.25	19.00	---	---	14.50	8.94	8.50	3.375	8.25	.875	6.88	1524
444TS	40.88	8.25	19.00	---	---	14.50	5.19	4.75	2.375	4.50	.625	3.00	1714
445T	44.62	8.25	19.00	16.50	---	---	8.94	8.50	3.375	8.25	.875	6.88	1730
445TS	40.88	8.25	19.00	16.50	---	---	5.19	4.75	2.375	4.50	.625	3.00	1714

(1)

- (1) SPECIAL DIMENSIONS APPLYING TO THIS ORDER ON THIS LINE.
(2) "D" VARIES — 250T - 320T +.00, -.03.
360T - 440T +.00, -.06.
(3) "U" VARIES — UP TO 1.625 DIA. +.0000, -.0005
1.625 AND LARGER +.000, -.001.
(4) ALL FRAMES HAVE EIGHT MOUNTING HOLES FOR DUAL MOUNTING.
(5) MOTOR WEIGHTS MAY VARY BY 15% DEPENDING UPON RATING.
(6) "N-W" VARIES +.00, -.25.
- FRAME- TYPE- CERTIFIED FOR-
ORDER- ITEM- HP- RPM- PH- HZ- VOLTS-
RELANCE SALES ORDER- APPROVED BY- DATE
- CONDUIT BOX LOCATED ON OPPOSITE SIDE WHEN F-2-W-1,
W-4,W-5,W-7, OR C-1 MOUNTING IS SPECIFIED.
IF MOUNTING CLEARANCE DETAILS ARE REQUIRED, CONSULT
FACTORY.
MAXIMUM PERMISSIBLE SHAFT RUNOUT WHEN MEASURED
AT END OF STD. SHAFT EXTENSION IS .002 T.I.R. UP TO
AND INCLUDING 1.625 DIA. AND .003 T.I.R. 1.625 DIA.
TO 5 INCH DIA.

CUSTOMER IS RESPONSIBLE FOR DETERMINING THAT BALDOR'S PRODUCT WILL PERFORM SUITABLY IN THE INTENDED APPLICATION.

REV. DESC: UPDATE TITLE SHEET 2			Baldor • Dodge • Reliance DIM SHEET 250T THRU 440T SH 1 of 1
REV. LTR: B	VERSION: 02	TDR: 000000498266	
FILE: \RAG\00000\167		REVISED: 07:05:46 04/29/2009	
MTL: —		BY: RAGEC	