

52A106982

3

A

THIRD ANGLE PROJECTION

VIEW SHOWING
P.E. VENTILATION
OPENINGS

5.61
MAX.

6.33
MAX.

.102

3.50
3.47
SOLID
OR
3.50
3.44
RESIL.

2.44

2.44

6.54

6.46

.91
.88

.500-14
CONDUIT
THREAD

C MAX.

L
MAX.

4.26
MAX.

N MIN.

W *

ZB

N-W

.188 X .188 X
(K) LG. KEY

.6250
.6245

.62 MIN.

2.75

1.505
1.495

4.31
4.19

1.95
1.83

.37
.34

1.505
1.495

I	KH	36	56	10.32	1.38	4.23	1.88	2.01/1.79	.69/.59
P	TYPE	GE SIZE	NEMA FR	C	K	L	N	N-W	ZB

SIGNATURES

DATE

MODEL

M.A.M.

10/09/89

DETAIL

.

.

CHECKED

.

.

ENGRG

.

.

MFG

.

.

QUALITY

.

.

ISSUED

C.C.P.

03/05/95

FOR ADDITIONAL INFO REFER TO:

APPLIED PRACTICES

DIMENSIONS ARE IN INCHES

MATERIAL

SOLID MODEL: 52A106982

REGAL

BELOIT

REGAL-BELOIT CORPORATION

TITLE

OUTLINE

FORM N - GENERAL PURPOSE MOTOR - DRIP PROOF -
SOLID OR RESIL. BASE - BALL OR SLEEVE BEARING FMF: 5KH39QN9631T

SIZE

DRAWING

52A106982

REV

3

SCALE: 0.250

REF. No: .

SHEET 1 of 1

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN WITHOUT CHANGE	04/28/92	BLJ
2	REDRAWN BY 2M SOFTWARE CO.	03/05/95	CCP
3	CHG TO RBC FORMAT PER ISO5-1777	02/15/06	SUDHA