



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR

(B-SS514570)

DASH	FRAME	B	C	2F	BS
2438	447TS	22.50	39.50	20.00	10.00
2938	449TS	27.50	44.50	25.00	12.50

NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH	PREV
7	SHAFT TOL WAS 2.376/2.375	KL 05-23-2005					
6	UPDATED DE BRACKET GEOMETRY CN 35521	DRS 09-13-2002					
5	ADDED OVERALL DIMENSIONS CN 27400-627	BJW 01-17-2000					
4	REVISED TO NEC CONDUIT BOX CN 28405	BJW 02-17-2000					
3	REMOVED NOTE FROM TITLE CN 16342	JHL 09-17-1993					
2	'C' DIM. WAS 39.44 & 44.44 CN 15854	JHL 06-09-1993					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP	WA			

TOLERANCES UNLESS SPECIFIED	DEC.	INCHES
.X		±.1
.XX		±.03
.XXX		±.005
.XXXX		±.0005

	DRAWN JHL 09-25-1992 CHK TB 09-25-1992 APPD JPN 10-27-1992 SCALE 9=64 REF FMF PREV
TITLE OUTLINE - STD. 447/9TS FR. - DR.PR. MAT'L FINISH CAD FILE SS514335	SIZE B DRAWING NO. SS514335 PAGE 7 OF 7 REV.