

52A103321

3

A

THIRD ANGLE PROJECTION

REV. 1

DESCRIPTION

DATE

APPROVED

2

CHG TO RBC FORMAT PER ISO5-1777

02/02/06

SUDHA

3

UPDATED AS PER ISAAC 06-0159

02/09/06

PRAVEEN.K

VIEW FACING LEAD END

5.61 MAX

2.49

2.37

1.57

.140

1.52

.115

2.25 MIN

KEYWAY FOR .188 X .188 X 1.75 KEY

4.500

4.497

.6250

.6245

.500-14 CONDUIT THREAD

FACE RUNOUT (WITH INDICATOR MOUNTED STATIONARY, RELATIVE TO SHAFT) MUST NOT EXCEED .010 TIR

ECCENTRICITY OF THIS SURFACE (WITH INDICATOR MOUNTED STATIONARY RELATIVE TO SHAFT) MUST NOT EXCEED .010 TIR

5.66 MAX

3.26 R MAX

2.077

2.938 R REF.

2.077

.375-16 UNC-2B (4 HOLES) .82 MIN. FULL THD. THESE HOLES FIT A GAGE HAVING A RABBIT 4.5005 DIA. AND 4 PINS .2917 DIA. LOCATED ON THE BASIC HOLE POSITIONS.

5	KH	37	56CZ	11.08	8.61	
4	KH	36	56CZ	10.68	8.21	
3	KH	35	56CZ	10.25	7.78	
2	KH	33	56CZ	9.87	7.40	
1	KH	32	56CZ	9.62	7.15	
PT	TYPE	GE SIZE	NEMA FR	C	AG	SHELL REF

SIGNATURES

DATE

MODEL

MDP

12/11/79

DETAIL

CHECKED

ENGRG

MFG

QUALITY

ISSUED

AAU

07/06/96

SOLID MODEL: 52A103321

REGAL BELOIT

REGAL-BELOIT CORPORATION

TITLE

OUTLINE

FORM "N" MOTOR-DRIP PROOF

R2 END MOUNTED-SLEEVE & BALL BEARING FMF 5KH37PN171

SIZE

DRAWING

52A103321

REV

3

SCALE: 0.250

REF. No:

SHEET 1 of 1