



- NOTES:
 1. CONDUIT BOX CAN ONLY BE ROTATED CLOCKWISE UP TO 270° FROM ITS ORIGINAL POSITION.
 2. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

5	CHANGED FRAME PER CN 40033	TAT 05-11-2008	ML	TOLERANCES UNLESS SPECIFIED		DRAWN SMC 04-15-1996
4	REDRAWN IN AUTOCAD	TAT 06-29-2004	ML	DEC INCHES		CHK MJA 04-19-1996
3	REVISED CONDUIT BOX COVER WIDTH WAS (15.20)	MRB 04-19-1999	X	±.1		APPR JPN 04-19-1996
2	REVISED HORIZONTAL LENGTH PER CASTING C' BOX		XX	±.03		SCALE 1:7
	PAD DIMENSION. 3" NPT WAS 3 1/2" NPT CN 23026	DMT 02-07-1997	XXX	±.005		REF
1	NEW DRAWING - DEV. ENG.	SMC 04-19-1996	XXXX	±.0005	MATL	FMF
NO	REVISION	BY & DATE	CHK	ANG ±7'30"	FINISH	PREV
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT					RFP	
					CAD FILE SS515578	REV
					DIST WA	5

DASH	FRAME	B	C	2F	2XF	BS
2875	447T	28.25	51.85		20.00	2.09
2875	449T	28.25	51.85	25.00		2.09