


1. MOTOR MUST BE ROTATED TO .75" STRIP SOCKET CLEARANCE FOR GROUND SCREW, MAXIMUM (10 DREGRES).

* DIM IS FROM RESIL RING
END CAP TO END OF SHAFT

4	REVISED STUD BOLT EXT. FROM 1.45" TO 1.53/1.37	NJS 11-05-2002	ML	TOLERANCES UNLESS SPECIFIED		DRAWN MH 12-05-1996			
	CN 24300-473			DEC. INCHES		CHK ML 12-06-1996			
3	REVISED STUD BOLT EXT. FROM 1.54/1.74 TO 1.45"	NJS 11-14-2001	.X	±.1		APPD GK 12-06-1996			
	CN 29400-662		.XX	±.03	TITLE OUTLINE	SCALE 1=2			
2	ADDED NOTE	CN 24378	PGK 06-09-1997	.XXX	56 FR. - EXP.PR. - TEFC - 1ø & 3ø	REF			
1	NEW DRAWING	CN 23099	MH 12-06-1996	.XXXX	MAT'L	FMF			
NO.	REVISION	BY & DATE	CHK	ANG	FINISH	PREV			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT					RFP	CAD FILE 104200			
					DIST WP	SIZE B	DRAWING NO. 104200	PAGE OF 4	REV. 4

ERROR: undefined
OFFENDING COMMAND: curre

STACK:

-dictionary-
/Pscript_WinNT_Compat
-dictionary-