


CATALOG NUMBER	OUTPUT RPM	FULL LOAD TORQUE LB.-IN.	F.L. AMPS	INPUT HP	RATIO TO 1	"XL"	"XH"
M1135286.00	250	46	2.6	1/4	7	13.16	8.84
M1135287.00	167	61	2.6	1/4	10.6	13.16	8.84
M1135288.00	115	85	2.6	1/4	15	13.16	8.84
M1135289.00	90	100	2.6	1/4	19	13.16	8.84
M1135290.00	58	158	2.8	1/4	30	13.16	8.84

08	OAL GEARBOX WAS 4.23 REF, XL DISTANCE WAS 13.07 PER ECR 80073	SMB 12/03/03	IPG	TOLEANCES UNLESS SPECIFIED	DEC.	INCHES	 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN SMB 08/27/03
07	ADDED 5.29 REF DIM TO SIDE VIEW PER ECR 82340	SMB 9/17/03	IPG	.X	±.1	CHK IPG 08/27/03		
06	REVISED F.L. AMP LOAD FOR MOTORS, OUTPUT SHAFT DIAMETER WAS .625, ECR 82339	SMB 9/10/03	IPG	.XX	±.03	APPD		
05	REVISED OUTLINE TO SHOW CORRECT SHAFT	SMB 9/8/03	IPG	.XXX	±.005	SCALE 1=2		
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	REF PR030237		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT					RFP	FINISH	TITLE	PREV
					DIST	CAD FILE	M1030897	SIZE B
							M1030897.00	REV. 08