



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
  2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
  3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	BS
1050	254U	10.25	23.27	8.25	4.12
1225	256U	12.00	25.02	10.00	5.00

		TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC		DRAWN MRB 08-20-1998						
		DEC.	INCHES			CHK	ML 08-20-1998					
3	REDRAWN IN AUTOCAD	TAT	05-19-2005	ML	.XX ±.03	APPD	TB 08-20-1998					
2	REV. OUTLINE TO HAVE CORR. COND. BOX. CN29200-711	KL	04-17-2001		.XXX ±.005	SCALE	1=4					
1	NEW DRAWING MU21547	MRB	08-20-1998		.XXXX ±.0005	REF						
NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	MAT'L	FMF					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						FINISH	PREV					
						RFP	CAD FILE ss203362	SIZE	DRAWING NO.	PAGE	OF	REV.
						DIST	LB	B	SS203362	3		3