

PE254T-7.5-6-575V


GENERAL PURPOSE ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
7.5	1200	254T	13.00	10.45	23.20	6.25	0.70	0.53	2.75	5.00	10.00	8.25	0.00	13.20	12.80	2.20	4.25

Shaft Extension, Key Set						Conduit Box		Bearings		Mount
U	V	R	S	ES	N-W	AA	AB	DE	ODE	
1.63	3.75	1.42	0.38	2.91	4.00	1.25	10.30	6309	6309	F1

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease. It is recommended that you add some additional lubrication when the motor is installed.

Three options (brands) for suitable lubrication include, but are not limited to, the following:

- 1.) Mobil Polyrex EM
- 2.) Citco Polyurea MP
- 3.) Conoco Phillips Polytac EP





PE254T-7.5-6-575V

GENERAL PURPOSE ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31


Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G

PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
7.5	1185	254T	575	60	1.15	F	B	1.3	H	TEFC	55	40° C

Amps (575V)		Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %	6309	6309	6 Lead Δ	272
7.8	50	91.0	91.0	89.5	89.5	0.740	0.660	0.530	33.7	185	280				

NAME PLATE

 North American Electric, Inc.								CONNECTION DIAGRAM 		
INVERTER DUTY 20:1 VT; 10:1 CT										
CAT NO:		PE254T-7.5-6-575V		HP	7.5	Hz	60	PHASE	3	
VOLTS		575		FLA	7.8		IP RATING		55	
RPM		1185		POWER FACTOR		0.74		DESIGN		B
FRAME		254T		NEMA NOM EFF		91.0		CODE		H
DRIVE END BEARING		6309		NEMA MIN EFF		89.5		S.F.		1.15
OPP DRIVE END BEARING		6309		MAX AMB		40° C		INS CLASS		F
ENCL		TEFC		RATING		CONT		SER		
MOTOR WEIGHT		272	LBS	CONNECTION		6 Lead Δ		LUB: Mobil Polyrex EM		
General purpose use on industrial machinery installed in damp, dusty or dirty environments.										
   CC 082A										
Hernando, Mississippi										

APPLICATIONS:

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments.