



PE324T-40-2


GENERAL PURPOSE ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
40	3600	324T	15.50	13.20	29.80	8.00	1.00	0.66	2.75	6.25	12.50	10.50	0.00	15.90	15.70	2.60	5.25

Shaft Extension, Key Set						Conduit Box		Bearings		Mount
U	V	R	S	ES	N-W	AA	AB	DE	ODE	
2.125	5.00	1.845	0.500	3.91	5.25	2.00	12.30	6312	6312	F1

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease. It is recommended that you add some additional lubrication when the motor is installed.

Three options (brands) for suitable lubrication include, but are not limited to, the following:

- 1.) Mobil Polyrex EM
- 2.) Citco Polyurea MP
- 3.) Conoco Phillips Polytac EP





PE324T-40-2

GENERAL PURPOSE ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31



Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G

PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
40	3545	324T	208-230/460	60	1.15	F	B	1.5	G	TEFC	55	40° C

Amps (460V)		Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %	6312	6312	12 Lead 2Δ/Δ	532
45.5	290	92.4	92.0	91.0	91.0	0.900	0.880	0.830	59.2	140	250				

NAME PLATE

 North American Electric, Inc.																				CONNECTION DIAGRAMS 208-230V 													
CAT NO: PE324T-40-2					FRAME 324T					PHASE 3																							
HZ 60		S.F. 1.15		HZ 50		S.F. 1.0		ENCL TEFC		IP 55																							
HP 40		RPM 3545		HP 40		RPM 2935		DUTY CONT		DES B																							
VOLTS 208-230/460				VOLTS 190/380				AMB 40° C		INS F																							
FLA 94.9 - 91 / 45.5				FLA 110/55				DE BEARING 6312																									
CODE G		P.F. 0.90		CODE F		P.F. 0.91		ODE BEARING 6312																									
EFF 92.4		MIN 91.0		EFF 90.7		MIN 89.3		LUB: Mobil Polyrex EM																									
MOTOR WEIGHT 532 LBS				CONNECTION 12 Lead 2Δ/Δ				SER NO																									
General purpose use on industrial machinery installed in damp, dusty or dirty environments.																						   CC 082A											
Hernando, Mississippi																																	

APPLICATIONS:

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments.