

PE365T-75-4


GENERAL PURPOSE ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
75	1800	365T	17.10	15.40	33.50	9.00	1.10	0.66	2.95	7.00	14.00	11.25	12.25	18.50	18.40	2.60	5.88

Shaft Extension, Key Set						Conduit Box		Bearings		Mount
U	V	R	S	ES	N-W	AA	AB	DE	ODE	
2.375	5.62	2.021	0.625	4.28	5.88	3.00	14.00	6313	6313	F1

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease. It is recommended that you add some additional lubrication when the motor is installed.

Three options (brands) for suitable lubrication include, but are not limited to, the following:

- 1.) Mobil Polyrex EM
- 2.) Citco Polyurea MP
- 3.) Conoco Phillips Polytac EP





PE365T-75-4

GENERAL PURPOSE ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31



Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G

PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
75	1780	365T	208-230/460	60	1.15	F	B	1.1	G	TEFC	55	40° C

Amps (460V)		Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %	6313	6313	12 Lead 2Δ/Δ	823
87.0	542	95.4	95.5	95.5	94.5	0.850	0.820	0.750	222.0	160	250				

NAME PLATE

 North American Electric, Inc.												CONNECTION DIAGRAMS 208-230V  460V 
INVERTER DUTY 20:1 VT; 10:1 CT												
CAT NO: PE365T-75-4				FRAME 365T				PHASE 3				
HZ 60		S.F. 1.15		HZ 50		S.F. 1.0		ENCL TEFC		IP 55		
HP 75		RPM 1780		HP 75		RPM 1480		DUTY CONT		DES B		
VOLTS 208-230/460				VOLTS 190/380				AMB 40° C		INS F		
FLA 193 - 174 / 87				FLA 210/105				DE BEARING 6313				
CODE G		P.F. 0.85		CODE F		P.F. 0.86		ODE BEARING 6313				
EFF 95.4		MIN 94.5		EFF 94		MIN 93.1		LUB: Mobil Polyrex EM				
MOTOR WEIGHT 823 LBS				CONNECTION 12 Lead 2Δ/Δ				SER NO				
General purpose use on industrial machinery installed in damp, dusty or dirty environments.												
   CC 082A												
Hernando, Mississippi												

APPLICATIONS:

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments.