



PE444T-75-8C


CRUSHER DUTY ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
75	900	444T	21.70	22.90	44.30	11.00	1.35	0.81	3.35	9.00	18.00	14.50	16.50	22.10	21.60	3.00	7.50

Shaft Extension, Key Set						Conduit Box		Bearings		Mount
U	V	R	S	ES	N-W	AA	AB	DE	ODE	
3.375	8.25	2.880	0.875	6.91	8.50	3.00	19.00	NU319	6318	F1

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease. It is recommended that you add some additional lubrication when the motor is installed.

Three options (brands) for suitable lubrication include, but are not limited to, the following:

- 1.) Mobil Polyrex EM
- 2.) Citco Polyurea MP
- 3.) Conoco Phillips Polytac EP





PE444T-75-8C

CRUSHER DUTY ELECTRIC MOTOR

NEMA PREMIUM EFFICIENCY

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31


Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G


PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
75	885	444T	208-230/460	60	1.15	F	C	1.7	G	TEFC	55	40° C

Amps (460V)		Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %	NU319	6318	12 Lead 2Δ/Δ	1353
95.0	542	93.6	93.6	92.5	92.4	0.800	0.720	0.600	445.0	200	240				

NAME PLATE

 North American Electric, Inc. 										CONNECTION DIAGRAMS 208-230V 
INVERTER DUTY 20:1 VT; 10:1 CT										
CAT NO: PE444T-75-8C			FRAME 444T			PHASE 3				
HZ 60		S.F. 1.15		HZ 50		S.F. 1.0		ENCL TEFC IP 55		
HP 75		RPM 885		HP 75		RPM 740		DUTY CONT DES C		
VOLTS 208-230/460			VOLTS 190/380			AMB 40° C		INS F		
FLA 210 - 190 / 95			FLA 230/115			DE BEARING NU319				
CODE G		P.F. 0.80		CODE F		P.F. 0.82		ODE BEARING 6318		
EFF 93.6		MIN 92.4		EFF 92		MIN 90.5		LUB: Mobil Polyrex EM		
MOTOR WEIGHT 1353 LBS			CONNECTION 12 Lead 2Δ/Δ			SER NO				
General purpose use on industrial machinery installed in damp, dusty or dirty environments.  CC 082A Hernando, Mississippi										

										460V 

APPLICATIONS:

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments.