



PE449TC-250-4C


GENERAL PURPOSE ELECTRIC MOTOR

HIGH EFFICIENCY / EISA COMPLIANT

THREE PHASE, TOTALLY ENCLOSED FAN COOLED - C-FLANGE W/ FEET

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
250	1800	449TC	21.70	31.40	52.80	11.00	1.35	0.81	3.35	9.00	18.00	20.00	25.00	23.00	23.40	3.00	16.00

FLANGE							Shaft Extension, Key Set						Conduit Box		Bearings		Mount
AH	AJ	AK	BB	BC	BD	BF	U	V	R	S	ES	N-W	AA	AB	DE	ODE	
8.25	14.00	16.00	0.25	0.25	18.00	8*5/8-11	3.375	8.25	2.880	0.875	6.91	8.50	3.00	19.90	6319	6318	F1

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease. It is recommended that you add some additional lubrication when the motor is installed.

Three options (brands) for suitable lubrication include, but are not limited to, the following:

- 1.) Mobil Polyrex EM
- 2.) Citco Polyurea MP
- 3.) Conoco Phillips Polytac EP





PE449TC-250-4C

GENERAL PURPOSE ELECTRIC MOTOR

HIGH EFFICIENCY / EISA COMPLIANT

THREE PHASE, TOTALLY ENCLOSED FAN COOLED - C-FLANGE W/ FEET

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31




Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G

PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
250	1790	449TC	460	60	1.15	F	C	0.6	G	TEFC	55	40° C

Amps (460V)		Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %	6319	6318	6 Lead Δ	2120
283	1825	95.0	94.1	94.5	94.0	0.870	0.860	2.830	738.0	200	230				

NAME PLATE

 North American Electric, Inc.										HIGH EFFICIENCY EISA COMPLIANT			CONNECTION DIAGRAMS (460V)						
INVERTER DUTY 20:1 VT; 10:1 CT																			
CAT NO: PE449TC-250-4C				FRAME 449TC				PHASE 3				Across The Line 							
HZ 60		S.F. 1.15		HZ 50		S.F. 1.0		ENCL TEFC		IP 55									
HP 250		RPM 1790		HP 250		RPM 1488		DUTY CONT		DES C		PWS Start 							
VOLTS 460				VOLTS 380				AMB 40° C		INS F									
FLA 283				FLA 348				DE BEARING 6319				PWS Run 							
CODE G		P.F. 0.87		CODE D		P.F. 0.87		ODE BEARING 6318											
EFF 95		MIN 94		EFF 93.5		MIN 92.4		LUB: Mobil Polyrex EM											
MOTOR WEIGHT 2120 LBS				CONNECTION 6 Lead Δ				SER NO				CC 082A							
General purpose use on industrial machinery installed in damp, dusty or dirty environments.																			
Hernando, Mississippi																			
  																			

APPLICATIONS:

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments.