




PE505UZ-300-4C

GENERAL PURPOSE ELECTRIC MOTOR

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
300	1800	505UZ	24.80	26.80	62.60	12.50	1.90	0.94	4.80	10.00	20.00	16.00	18.00	26.60	24.30	4.50	8.50

Shaft Extension, Key Set						Conduit Box		Bearings		Mount
U	V	R	S	ES	N-W	AA	AB	DE	ODE	
3.875	10.88	3.309	1.000	10.00	11.63	3.00	21.30	NU322	6319	F1

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease. It is recommended that you add some additional lubrication when the motor is installed.

Three options (brands) for suitable lubrication include, but are not limited to, the following:

- 1.) Mobil Polyrex EM
- 2.) Citco Polyurea MP
- 3.) Conoco Phillips Polytac EP





PE505UZ-300-4C

GENERAL PURPOSE ELECTRIC MOTOR

TOTALLY ENCLOSED FAN COOLED

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G

PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
300	1790	505UZ	460	60	1.15	F	C	0.6	G	TEFC	55	40° C

Amps (460V)		Efficiency (%)				Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	Min.	100%	75%	50%	FLT	LRT %	BDT %				
330.0	2200	96.2	95.8	95.4	95.4	0.870	0.850	0.750	880.0	200	280	NU322	6319	6 Lead Δ	2600

NAME PLATE

 AC INDUCTION MOTOR INVERTER DUTY 20:1 VT; 10:1 CT										CONNECTION DIAGRAMS (460V)				
										Across The Line				
										T7 T8 T9				
										T1 T2 T3				
										L1	L2	L3		
CAT NO: PE505UZ-300-4C										FRAME 505UZ		PHASE 3		
HZ 60		S.F. 1.15		HZ 50		S.F. 1.0		ENCL TEFC		IP 55				
HP 300		RPM 1790		HP 300		RPM 1490		DUTY CONT		DES C				
VOLTS 460				VOLTS 380				AMB 40° C		INS F				
FLA 330.0				FLA 400				DE BEARING NU322						
CODE G		P.F. 0.87		CODE F		P.F. 0.89		ODE BEARING 6319						
EFF 96.2		MIN 95.4		EFF 95.4		MIN 94.5		LUB: Mobil Polyrex EM						
MOTOR WEIGHT 2600.0 LBS				CONNECTION 6 Lead Δ				SER NO						
General purpose use on industrial machinery installed in damp, dusty or dirty environments. ISO9001 CERTIFIED CE CS® C US Hernando, Mississippi												PWS Start		
												T7 T8 T9		
												T1 T2 T3		
												L1	L2	L3
												PWS Run		
												T7 T8 T9		
												T1 T2 T3		
												L1	L2	L3

APPLICATIONS:

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments.