

SS56C2M-2-RB


WASHDOWN DUTY MOTOR

HIGH EFFICIENCY / EISA COMPLIANT

STAINLESS STEEL CONSTRUCTION - ROUND BODY (C-FLANGE FOOTLESS)

TOTALLY ENCLOSED FAN COOLED - IP66 CONSTRUCTION

INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31



| DIMENSIONS | | | | | | | | | | | | |
|------------|------|-------|----------|------|-------|-------|------|------|------|-----|------|----------|
| HP | RPM | Frame | Mounting | | | | | | | | | |
| | | | C | P | AK | AJ | AH | AG | BA | BB | BC | BF |
| 2 | 3600 | 56C | 11.59 | 6.50 | 4.500 | 5.875 | 2.06 | 9.53 | 0.16 | N/A | 9.53 | 4*3/8-16 |

| Shaft Extension, Key Set | | | | | Conduit Box | | | | Bearings | | Mount |
|--------------------------|-------|-------|------|------|-------------|------|------|------|----------|------|-------|
| U | R | S | ES | N-W | AA | AB | AC | BV | DE | ODE | |
| 0.625 | 0.517 | 0.188 | 1.41 | 1.88 | 0.86 | 5.75 | 4.25 | 5.30 | 6205 | 6205 | F1 |

BEARING LUBRICATION: The bearings come lubricated with Mobile Polyrex EM Polyurea Grease.



SS56C2M-2-RB

WASHDOWN DUTY MOTOR
HIGH EFFICIENCY / EISA COMPLIANT
STAINLESS STEEL CONSTRUCTION - ROUND BODY (C-FLANGE FOOTLESS)
TOTALLY ENCLOSED FAN COOLED - IP66 CONSTRUCTION
INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31

PERFORMANCE DATA

| HP | RPM | Frame | Voltage | Frequency (Hz) | Full Load S.F. | Insulation Class | NEMA Design | Slip (%) | NEMA Code | Enclosure Type | IP Rating | Max. Ambient |
|----|------|-------|-------------|----------------|----------------|------------------|-------------|----------|-----------|----------------|-----------|--------------|
| 2 | 3480 | 56C | 208-230/460 | 60 | 1.15 | F | C | 3.3 | K | TEFC | 66 | 40° C |

| Amps (460V) | | Efficiency (%) | | | | Power Factor | | | Torque (ft-lb) | | | DE Bearing | ODE Bearing | Connection | Weight (lbs.) |
|-------------|------|----------------|------|------|------|--------------|------|------|----------------|-------|-------|------------|-------------|-------------|---------------|
| FLA | LRA | 100% | 75% | 50% | Min. | 100% | 75% | 50% | FLT | LRT % | BDT % | | | | |
| 2.4 | 25.0 | 84.0 | 79.0 | 75.0 | 81.5 | 0.91 | 0.85 | 0.78 | 2.9 | 285 | 300 | 6205 | 6205 | 9 Lead 2Y/Y | 46 |

NAME PLATE

| | | | | | | | |
|---|------------------------|--|-----------------|---------------------------------------|-------|----------------------------|--|
| | | WASHDOWN DUTY STAINLESS STEEL MOTOR | | | | CONNECTION DIAGRAMS | |
| INVERTER DUTY 20:1 VT; 10:1 CT | | | | HIGH EFFICIENCY EISA COMPLIANT | | | |
| CAT NO: SS56C2M-2-RB | | FRAME 56C | | PHASE 3 | | | |
| HZ 60 | S.F. 1.15 | HZ 50 | S.F. 1.2 | ENCL TEFC | IP 66 | | |
| HP 2 | RPM 3480 | HP 1.5 | RPM 2870 | DUTY CONT | DES C | | |
| VOLTS 208-230/460 | | VOLTS 190/380 | | AMB 40° C | INS F | | |
| FLA 5.3 - 4.8 / 2.4 | FLA 4.4/2.2 | | DE BEARING 6205 | | | | |
| CODE K | P.F. 0.91 | CODE K | P.F. 0.92 | ODE BEARING 6205 | | | |
| EFF 84.0 | MIN 81.5 | EFF 81.5 | MIN 78.5 | LUB: Mobile Polyrex EM | | | |
| MOTOR WEIGHT 46 LBS | CONNECTION 9 Lead 2Y/Y | | SER NO | | | | |
| Special purpose motor designed for washdown applications and extremely corrosive environments. Hernando, Mississippi | | | | | | CC 082A | |

APPLICATIONS:

Applications include washdown applications, food processing, chemical processing, pharmaceuticals, poultry processing, meat processing, dairy applications, bakeries, snack foods, bottling and extremely corrosive environments.