



037660

TERM.
END

NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90 ° STEPS.
2. CONDUIT BOX CAN BE MOUNTED IN OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °. THIS MODIFICATION CAN BE PERFORMED ONLY BY THE ORIGINAL EQUIPMENT MANUFACTURER, OR BY A FACILITY THAT IS COVERED UNDER UNDERWRITERS LABORATORIES INC. CATEGORY PTKQ, TITLED "MOTOR AND GENERATORS, REBUILT FOR USE IN HAZARDOUS LOCATION".
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1212	213/215	22.63	11.76	10	7	5
912	213/215	19.63	8.63	7	5.5	3.5
DASH	FRAME	C	B	2F	2FF	BS

						TOLERANCES UNLESS SPECIFIED		DRAWN AK 10/28/2009					
					DEC	INCHES		CHK	SK 10/28/2009				
					X	±.1		APPR					
					XX	±.02		SCALE	1:8				
02	UPDATED PER IS12-0462	GR	2/15/2012	PN	XXX	±.005	TITLE OUTLINE 210 FR. - EPFC	REF	SS84370				
01	ADDED F2 MOUNTING VIEW	PN	12/30/2010	SR	XXXX	±.0005		MATL	FMF 215TTGN4026				
NO	REVISION	BY & DATE	CHK	ANG	±730"	FINISH		PREV					
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT							CAD FILE	037660	SIZE B	DRAWING NO	037660	REV	02