



HOLES IN LUGS MUST BE CONCENTRIC WITH ONE ANOTHER WITHIN .020

TOTALLY ENCLOSED MOTOR FULLY GASKETED

DASH	FR	C
525	48	9.81
550	48	10.06
600	48	10.56
625	48	10.81
650	48	11.06
675	48	11.31

				TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC	DRAWN BJW 11-22-1999	
				DEC.	INCHES		CHK	ML 11-23-1999
				.X	±.1		APPD	SAT 11-24-1999
3	REDRAWN IN AUTOCAD	TAT 10-15-2004	ML	.XX	±.03	TITLE OUTLINE	SCALE	3=8
2	ROT. CAP. 60° & ADD'D DRAIN HOLE PLUGS MU27937	NJS 11-03-2000		.XXX	±.005	48 FR.	REF	
1	NEW DRAWING MU27937	BJW 11-24-1999		.XXXX	±.0005	MAT'L.	FMF	
NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH	PREV	
			RFP			CAD FILE ss403014	SIZE	DRAWING NO. PAGE OF
			DIST	WP			A	SS403014 3

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT