



- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.  
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	2FF	BS
1525	404T	14.75	35.62	12.25		6.12
1675	404/405T	16.25	37.14	12.25	13.75	6.88

NO		REVISION	BY & DATE	CHK	ANG	TOLERANCES UNLESS SPECIFIED	marathon electric		DRAWN	TLB 05-19-1988
8	ADD F2 VIEW		CRJ 11/30/2011			DEC INCHES			CHK	FG 05-20-1988
7	UPDATED FRAME & REDRAWN IN SOLIDWORKS MU102119		JSB 09-13-2011	JB	X	±.1			APPR	ML 05-22-1988
6	UPDATED FRAME & ADDED INFO ON 27430		KL 04-05-2004		XX	±.03	TITLE	OUTLINE-TEFC	SCALE	1:5
5	ADDED NEW Ø DIM		MRB 09-12-1996		XXX	±.005	400T FR.-TAPPED LEAD HOLE		REF	
4	REDRAWN ON CADD		TBL 05-22-1988		XXXX	±.0005	MATL		FMF	MU105350
						±.730"	FINISH		PAGE	OF
			THIRD ANGLE PROJECTION			RFP	PREV	SIZE	DRAWING NO	REV
						NETWORK FILE NAME	SS508859	B	SS508859	8