



- NOTES:
 1) MAXIMUM FACE RUNOUT .004 T.I.R.
 2) MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 3) PERMISSIBLE SHAFT RUNOUT .002 T.I.R.
 4) GASKETS THROUGHOUT.

056E17T2005	11.77	9.71	8.78	24	1/2	1800
056E17T2004	11.77	9.71	8.78	12	1/2	1800
056E17T2003	10.77	8.71	7.78	24	1/3	1800
056E17T2002	10.77	8.71	7.78	12	1/3	1800
056E17T2001	10.27	8.21	7.28	12	1/4	1800
CATALOG No.	"C"	"L"	"AD"	VOLTS	H.P.	RPM

		TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC		DRAWN IPG 6/10/08	
		DEC INCHES				CHK BC 6/10/08	
		X ±.1				APPR	
02	ADDED 056E17T2001 TO TABLE	IPG 5/13/2010	SK XX ±.03	TITLE OUTLINE		SCALE 1:2	
01	ADDED CAT NOS. 056E17T2002, 056E17T2003 & 056E17T2005	RBP 1/9/2009	BC XXX ±.005	48 FRAME DC		REF 031880	
--	RELEASED: REF. 031880 & 031672	IPG 6/10/2008	BC XXXX ±.0005	MATL		FMF 056E17T2004	
NO	REVISION	BY & DATE	CHK ANG ±1/2°	FINISH		PAGE OF	
THIRD ANGLE PROJECTION			RFP	PREV		SIZE	DRAWING NO
			NETWORK FILE NAME 031906		B	031906	REV 02