

SS88643

(C)

(AG)

.31
.25

3.12

.31x.31x2.38
KEY

(6.13)

- A -

BS

$\phi 8.500$
 $\phi 8.497$

$\phi 1.3750$
 $\phi 1.3745$

.004 A

$\phi 1.13$ LEAD HOLE

.25

.004 A

5.50

5.50

7.00

(8.00)

4.25

(12.25)

(9.50)

(6.25)

(6.12)

45°

45°

$\phi 7.265$
 $\phi 7.235$

2.00

(11.64)

5.25

5.19

.18

4.25

8.50

(9.50)

$\phi .41-.46$
8 HOLES

1/2-13 UNC-2B
.75 FULL THD.
4 HOLES

1. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.
2. CONDUIT BOX CAN BE MOUNTED OM OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180.
(EXCEPT AS NOTED)
3. DASH 965 TO BE READ FROM OPPOSITE SHAFT END

DASH	FRAME	C	AG	BS	MOUNTING
1115	213/15TC	18.03	14.91	6.30	F1 / F2
1240	213/15TC	19.28	16.16	7.55	F1 ONLY

				TOLERANCES UNLESS SPECIFIED			DRAWN UD 01/31/13	
				DEC.	INCHES		CHK SM 01/31/13	
				.X	±.1		APPD	
				.XX	±.03		SCALE 1=5	
				.XXX	±.005		REF SS88643LE	
				.XXXX	±.0005	MAT'L.	FMF MU108472	
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT – DO NOT SCALE THIS PRINT			RFP		CAD FILE SS88643LN	SIZE	DRAWING NO. PAGE 1 OF 1	REV.
			DIST LB			A	SS88643LN	